

LEGEND	
 100 100	BOUNDARY LINE/ R.O.W. (EXISTING) BOUNDARY LINE/ R.O.W. (ABUTTING) 1-FOOT LIDAR CONTOUR (OBTAINED FROM VCGI DATABASE) 1-FOOT GROUND SURVEY CONTOUR
dl dl S S FM FM W W	1-INCH DIAMETER CL200 POLYETHYLENE PLASTIC WATER LINE (UNLESS OTHERWISE NOTED) WELL ISOLATION WASTEWATER ISOLATION
WL WB UE GAS tel ohw	WETLAND BOUNDARY WETLAND BUFFER UNDERGROUND ELECTRICAL CONDUIT UNDERGROUND GAS LINE UNDERGROUND TELEPHONE LINE UTILITY POLE/ OVERHEAD WIRES
	SURVEY TRAVERSE STATION TEMPORARY BENCHMARK (TYPE AND ELEVATION NOTED) TEST PIT (TP-01)
W Y	DRILLED WELL (UNLESS OTHERWISE NOTED) LIGHT POST

DRILLED WELL LEAKAGE, PRESSURE TESTING AND DISINFECTION:

LEAKAGE & PRESSURE TESTING: (PURSUANT TO §1-1209 OF THE CURRENT EPR)

(A) WATER SERVICE LINES AND WATER SERVICE PIPES SHALL BE PRESSURE TESTED AND LEAKAGE TESTED ACCORDING TO ONE OF THE FOLLOWING PROCEDURES PRIOR TO PLACING THE POTABLE WATER SUPPLY INTO SERVICE:

(1) VERMONT PLUMBING RULES;

PIPE OR STRUCTURE RETESTED.

- (2) THE AWWA; OR
- (3) BY PRESSURIZING THE LINES AND PIPES WITH WATER AT THE WORKING PRESSURE OF THE SYSTEM OR GREATER AND HOLD WITHOUT A DROP IN PRESSURE FOR A MINIMUM OF 16 MINUTES.

(B) ATMOSPHERIC STORAGE STRUCTURES SHALL BE LEAKAGE TESTED ACCORDING TO THE FOLLOWING PROCEDURE TO ENSURE WATER LOSS IS EQUAL TO OR LESS THAN 0.05 OF 1 PERCENT OF THE TANK CAPACITY PRIOR TO PLACING THE STRUCTURE INTO SERVICE:

(1) FILLING THE TANK WITH POTABLE WATER AND LET STAND FOR 24 HOURS; AND (2) MEASURING THE LOSS OF WATER OVER 24 HOURS.

(C) IF THE WATER SERVICE LINE, WATER SERVICE PIPE, OR ATMOSPHERIC STORAGE STRUCTURE FAILS THE PRESSURE OR LEAKAGE TEST, THE CAUSE OF THE FAILURE SHALL BE REPAIRED, AND THE LINE,

DISINFECTION: (PURSUANT TO §1-1210 OF THE CURRENT EPR)

DISPOSING OF THE CHLORINATED WATER.

(A) THE DRILLED WELL SHALL BE DISINFECTED PURSUANT TO THE REQUIREMENTS OF SUBSECTION (B). (C), AND (D) PRIOR TO PLACING THE WELL INTO SERVICE AND AFTER ANY SERVICING OR REPAIR OF THE WELL, SUCH AS INSTALLATION OF NEW PIPES, WIRES, CASING, OR PUMPS

(B) DISINFECTION OF THE DRILLED WELL SHALL BE COMPLETED PURSUANT TO THE RECOMMENDATIONS BY THE VERMONT DEPARTMENT OF HEALTH FOR DISINFECTING A WATER SYSTEM, OR THE FOLLOWING METHOD:

- (1) FLUSH THE WELL UNTIL THE WATER RUNS CLEAR; (2) PROVIDE AN ADDITIONAL DOSAGE OF AT LEAST 100 MG/L OF CHLORINE IN THE WELL;
- (3) CIRCULATE THE WATER IN THE WELL; AND (4) ALLOW THE WATER TO REST IN THE WELL FOR A MINIMUM OF 12 TO 24 HOURS BEFORE

(C) DISINFECTION OF THE WATER SERVICE LINES AND WATER SERVICE PIPES SHALL BE COMPLETED PURSUANT TO THE REQUIREMENTS OF THE VERMONT PLUMBING RULES OR THE FOLLOWING METHOD:

- (1) FILL THE WATER SERVICE LINE OR WATER SERVICE PIPE WITH A WATER/CHLORINE SOLUTION OF 100 MG/L; AND
- (2) ALLOW THE CHLORINATED WATER TO REST IN THE WATER SERVICE LINE OR WATER SERVICE PIPE FOR A MINIMUM OF 24 HOURS BEFORE DISPOSING OF THE CHLORINATED WATER.

(D) DISINFECTION OF WATER STORAGE TANKS SHALL BE COMPLETED PURSUANT TO AWWA STANDARD C652.

(E) CHLORINATED WATER USED TO DISINFECT OR RESULTING FROM DISINFECTION OF THE DRILLED WELL SHALL NOT BE DISCHARGED TO A WASTEWATER SYSTEM OR TO SURFACE WATER. PROPER DISPOSAL OF THE CHLORINATED WATER IS TO THE GROUND SURFACE THROUGH SHEET FLOW THAT INFILTRATES INTO THE SOIL OR DISPOSAL TO A WASTEWATER TREATMENT FACILITY, IF AUTHORIZED BY THE WASTEWATER TREATMENT FACILITY.



LOT 1 EDEN SAND & GRAVEL COMPANY, INC. EXISTING LOT 1: 39.6 ± ACRES PROPOSED LOT 1: 38.1 ± ACRES

N/F

Lands of

OWNER:

EDEN SAND & GRAVEL

DEED - VOL. 228, PG. 39

DRAFT

JASON S. BARNARD

SPAN #519-163-10908

PARCEL ID #KR0854

COMPANY, INC.

SIGNATURE: